

# MIN 2500~6000 TL-X

- Maximum efficiency 98.4%
- Dual MPP trackers
- Type II SPD on DC side
- Supports export control
- Touch key and OLED display
- AFCI function ready



**GROWATT**

[www.ginverter.com](http://www.ginverter.com)

P O W E R  
- I N G O  
T O M O -  
R R O W O

Datasheet	MIN 2500TL-X	MIN 3000TL-X	MIN 3600TL-X	MIN 4200TL-X	MIN 4600TL-X	MIN 5000TL-X	MIN 6000TL-X
<b>Input data (DC)</b>							
Max. recommended PV power (for module STC)	3500W	4200W	5040W	5880W	6440W	7000W	8100W
Max. DC voltage	500V	500V	550V	550V	550V	550V	550V
Start voltage				100V			
Nominal voltage				360V			
MPP voltage range	80V-500V	80V-500V	80V-550V	80V-550V	80V-550V	80V-550V	80V-550V
No. of MPP trackers				2			
No. of PV strings per MPP tracker				1			
Max. input current per MPP tracker				13.5A			
Max. short-circuit current per MPP tracker				16.9A			
<b>Output data (AC)</b>							
AC nominal power	2500W	3000W	3600W	4200W	4600W	5000W	6000W
Max. AC apparent power	2500VA	3000VA	3600VA	4200VA	4600VA	5000VA	6000VA
Nominal AC voltage(range*)	230V (180-280V)						
AC grid frequency(range*)	50/60 Hz (45-55Hz/55-65 Hz)						
Max. output current	11.3A	13.6A	16A	19A	20.9A	22.7A	27.2A
Adjustable power factor	0.8leading...0.8lagging						
THDI	<3%						
AC grid connection type	Single phase						
<b>Efficiency</b>							
Max. efficiency	98.2%	98.2%	98.2%	98.4%	98.4%	98.4%	98.4%
European efficiency	97.1%	97.1%	97.2%	97.5%	97.5%	97.5%	97.5%
MPPT efficiency	99.9%						
<b>Protection devices</b>							
DC reverse polarity protection				Yes			
DC switch				Yes			
DC/AC surge protection				Type II / Type III			
Insulation resistance monitoring				Yes			
AC short-circuit protection				Yes			
Ground fault monitoring				Yes			
Grid monitoring				Yes			
Anti-islanding protection				Yes			
Residual-current monitoring unit				Yes			
AFCI protection				Yes			
<b>General data</b>							
Dimensions (W / H / D)				375/350/160mm			
Weight				10.8kg			
Operating temperature range				-25°C ... +60°C			
Nighttime power consumption				<1W			
Topology				Transformerless			
Cooling				Natural convection			
Protection degree				IP65			
Relative humidity				0-100%			
Altitude				4000m			
DC connection				H4/MC4(Optional)			
AC connection				Connector			
Display				OLED+LED/WIFI+APP			
Interfaces: RS485 / USB/Wi-Fi/ GPRS/ RF/LAN				Yes/Yes/Optional/Optional/Optional /Optional			
Warranty:10 years				Yes			

CE, CEI 0-21, VDE-AR-N 4105, VDE 0126-1-1, UTE C 15-712-1, EN 50549, IEC 62116, IEC 61727, G99, C10/C11, UNE217001, UNE206007, PO12.2

\* The AC voltage and frequency range may vary depending on specific country grid standard.  
All specifications are subject to change without notice.