

4G Module

GoodWe 4G Module is easy to install with Plug-Play design and can support several operators worldwide, offering customers convenience and reliability especially in remote areas without access to Wi-Fi.



Technical Data

| Basic Parameter | 4G Kit-EC | 4G Kit-AU |
|----------------------------|-----------|-----------|
| Power Supply(V) | 5 | 5 |
| Self-Consumption (W) | <4 | <4 |
| Operating temperature (°C) | -30~60 | -30~60 |
| Operating Humidity | 0~100% | 0~100% |
| Altitude (m) | ≤4000 | ≤4000 |
| Size (L*W*H) (mm) | 96×49×32 | 96×49×32 |
| Protection Class | IP65 | IP65 |

| Wireless Parameter | | |
|--------------------|----------------------|--------------------|
| LTE-FDD | B1/B3/B7/B8/B20/B28A | B1/B3/B5/B7/B8/B28 |
| LTE-TDD | - | B40 |
| WCDMA | B1/B8 | B1/B2/B5/B8 |
| GSM/GPRS | B3/B8 | B3/B8 |
| Certification | CE | RCM |

| Transmission Speed | | |
|--------------------|---------------------|---------------------|
| LTE-FDD(Mbps) | 150 (DL)/ 50 (UL) | 150 (DL)/ 50 (UL) |
| LTE-TDD(Mbps) | - | 130 (DL)/ 30 (UL) |
| WCDMA(Kbps) | 384 (DL)/ 384 (UL) | 384 (DL)/ 384 (UL) |
| GPRS(Kbps) | 107 (DL)/ 85.6 (UL) | 107 (DL)/ 85.6 (UL) |