

MONO CRYSTALLINE DOUBLE-GLASS HALF CUT BIFACIAL MODULE

530 / 535 / 540 / 545 / 550 Watts

Black Panther




Overview

Ground breaking technology; higher power output, improved system performance - the ideal solution for end users who want a fast turnaround on their investments. A fully certified premium quality and high efficiency module made with A Grade materials.

Key Benefits

	Certified by Independent Engineering Bodies		Product Liability Insurance
	Ultra High Power Output		15 Years Limited Product Warranty
	Low Resistive Losses		Higher Light Conversion



Guaranteed mechanical resistance to severe weather conditions



Positive Tolerance




100 % electro-luminescence tested

Tests, Certifications and Warranties

Standard Tests	IEC 61215, IEC 61730
Factory Quality Tests	ISO 9001: 2015, ISO 14001: 2015
Certifications	Conformity to CE, PV CYCLE Fire safety Class C according to UL790
Insurance	Product liability insurance provided by Allianz
Wind and Snow Loads Testing	Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal)
Power Tolerance	Guaranteed +0%/+5% (STC condition)
Warranties	<ul style="list-style-type: none"> 15-year limited product warranty 15-year manufacturer warranty on 91.84% of the nominal performance 30-year transferable linear power output warranty

Linear Performance Warranty



First Year Output $\geq 98.0\%$ 2-30 Year Decline $\leq 0.44\%$ 30 Year Output $\geq 85.24\%$

MONO CRYSTALLINE DOUBLE-GLASS HALF CUT BIFACIAL MODULE

RCM-xxx-7BMF (xxx=530-550)

Electrical Characteristics

POWER CLASS ⁽¹⁾			530		535		540		545		550	
Testing Condition			STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power	Pmax	[Wp]	530	394,44	535	398,16	540	401,88	545	405,61	550	409,33
Maximum Power Voltage	Vmp	[V]	40,45	37,63	40,58	37,75	40,71	37,88	40,84	38,00	40,97	38,12
Maximum Power Current	Imp	[A]	13,11	10,48	13,19	10,55	13,27	10,61	13,35	10,68	13,43	10,74
Open Circuit Voltage	Voc	[V]	49,00	46,25	49,16	46,40	49,32	46,55	49,48	46,70	49,63	46,85
Short Circuit Current	Isc	[A]	13,80	11,14	13,88	11,21	13,97	11,28	14,05	11,35	14,14	11,42
Module Efficiency	Eff	[%]	20,54		20,73		20,93		21,12		21,31	
Maximum Series Fuse	IR	[A]	25									
Maximum System Voltage	VSys	[V]	1500 V (IEC)									
<i>(1) Measurement Tolerances: Pmax (± 3%), Isc & Voc (± 5%) - Power Classification 0/+5W</i>												
<i>(2) STC (Standard Testing Condition): Irradiance 1000W/m², Cell Temperature 25°C, AM 1.5</i>												
<i>(3) NMOT (Nominal Operating Module Temperature): Irradiance 800W/m², NMOT, Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s</i>												

Bi Facial Output (4)


POWER CLASS			530		535		540		545		550	
			P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]	P _{max} [Wp]	Eff [%]
Power with Backside Gain	+5	[%]	556,5	21,6	561,8	21,8	567,0	22,0	572,3	22,2	577,5	22,4
	+10	[%]	583,0	22,6	588,5	22,9	594,0	23,1	599,5	23,3	605,0	23,5
	+15	[%]	609,5	23,7	615,3	23,9	621,0	24,1	626,8	24,3	632,5	24,6
	+20	[%]	636,0	24,7	642,0	24,9	648,0	25,2	654,0	25,4	660,0	25,6
	+25	[%]	662,5	25,7	668,8	26,0	675,0	26,2	681,3	26,4	687,5	26,7
	+30	[%]	689,0	26,7	695,5	27,0	702,0	27,2	708,5	27,5	715,0	27,8

(4) Bifaciality Factor > 70% - Back-side power gain depends upon the specific project albedo - Efficiency is according to the surface of the module

Mechanical Data

Dimensions	2278mm x 1133mm x 35mm
Weight	39 Kg
Cell Type	Mono Perc – 182mm x 91mm (2x72 Pcs) – M10
Front Glass	2.0 mm Tempered and low iron glass + ARC
Rear Side	2.0 mm Tempered and low iron glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 – 3 Bypass Diodes
Connector	EV02 compatible
Output cable	4mm ² - Length = 1200mm or customized

Dimensions




RECOM assumes no liability or responsibility for any typographical error, layout error, misinformation, any other error, omission, contained herein.

recom-solar.com

I-V Curve

The module relative power loss at low light irradiance of 200W/m² is less than 3%.



Temperature Characteristics

P _{max} Temperature Coefficient	-0.348% / °C
V _{oc} Temperature Coefficient	-0.282% / °C
I _{sc} Temperature Coefficient	+0.05% / °C
Operating Temperature	-40~+85 °C
Nominal Operating Module Temperature (NMOT)	42 ± 2 °C

Packing Configuration

Container	40'HC
Pieces per Pallet	30
Pallets per Container	20
Pieces per Container	600

The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to on-going innovation, research and product enhancement, RECOM Solar reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein. Please read the safety and installation instructions before using the modules.

© Copyright 2021. RECOM